

SAUGATUCK TOWNSHIP FIRE DISTRICT

THE DISTRICT

Proudly serving: Douglas | Saugatuck | Saugatuck Township

3342 Blue Star Highway Saugatuck, MI 49453 Phone: 269 857-3000 E-mail: office@saugatuckfire.org

REQUIREMENTS FOR TENT STRUCTURES

Date:	Location:
Address: _	Municipality:
	s a partial check list of requirements based on the International Fire Code 2015 C). If you have further requirements consult with Saugatuck Twp. Fire District.
Check off	when complete:
be p	tailed site and floor plan for tents with an occupant load of 50 or more shall provided with each application for approval. The floor plan shall indicate details means of egress, seating capacity, arrangement of seating and tion of any heating and electrical equipment. (3103.6)
Fire	apparatus access roads shall be provided. (3103.8.1 / 503)
vehi	is shall not be located within 20 feet of lot lines, buildings, other tents, parked cles, or internal combustion engines. Support ropes and guy wires shall be sidered as part of the tent. Note: There are exceptions, consult with the gatuck Township Fire District. (3103.8.2)
free	nobstructed fire break passageway or fire road not less than 12 feet wide and from guy ropes, or other obstructions shall be maintained on all sides of all ss. (3103.8.6)
	ents and side curtains shall be composed of flame resistant material in ordance with NFPA 701 and IFC. (3104.2)
	s shall have a permanently affixed label bearing the identification of size and ic or material type. (3104.3)
	py of the certificate attesting to the flame resistance of the fabric shall be mitted to Saugatuck Township Fire District. (3104.4)
Com	bustible materials shall not be located within any tent structure. (3104.5)
	n flame or other devices emitting flame, fire or heat including parked cars I not be permitted inside or within 20 feet of the tent. (3104.7)



SAUGATUCK TOWNSHIP FIRE DISTRICT



Proudly serving: Douglas | Saugatuck | Saugatuck Township

Portable fire extinguishe of 2A10BC. (3104.12	ers shall be provided at the exit 2 /906)	s. A minimum rating size	
The occupant load shall be stated. (3104.14 / Chapter 10)			
Side curtains shall be flame resistant and when used at exit openings shall be of a color that contrasts with the color of the tent. (3103.12.3)			
seating areas and aisles	width of not less than 44 inche shall progressively increase in v isle width for each 50 persons s	width to provide, at all points,	
A minimum number of m (3102.12.5.1)	eans of egress and means of eg	ress widths are as follows:	
Occupant Load 10-199 200-499	Min. # of Means of Egress 2 3	Min. Width of Egress 72" 72"	
Exits shall be clearly marked if the occupant load is 50 or more. (3103.12.6)			
Exit signs shall be approved self-luminous type or shall be internally or externally illuminated. (3103.12.6.1)			
Means of egress shall be illuminated. (3103.12.7)			
Required width of exits, aisles and passageways shall be maintained at all times. (3103.12.8)			
Trained crowd manager/supervisor shall be provided at a ratio of one crowd manager/supervisor for every 250 occupants. (3104.20.2)			
"No Smoking" signs shall be posted in conspicuous locations. (3104.6)			
Provide STFD with a copy of the "Miss Dig" ticket number and documentation for location and marking of underground utilities where tent will be erected. (102.9)			
Saugatuck Township Fire District will inspect the tent installation.			
Signature of Applicant:			
Signature of Fire Inspector:			
Date: Revised 8/2016-CM			